Technical Data Sheet

SAR Lubricants

Last Updated: 09.12.2015 Code: AT0407 /AT0407U

AGRISTAR UTTO is a high performance Universal Tractor Transmission Oil designed to provide exceptional protection to agricultural and off highway equipment especially those operating under severe load conditions.

APPLICATION

Use as received where a common lubricant for transmissions, differentials, final drives, hydraulic and wet brake applications is required.

BENEFITS

- Excellent extreme pressure (EP) performance maximizes component life
- Formulated to provide exceptional anti-wear and anti-corrosion capabilities
- Strong yellow metal protection and multi-metal capability minimises stock inventories
- Excellent thermal stability promotes greater oxidation control for longer fluid life
- Suitable for wet brakes and PTO applications

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API GL-4
- John Deere J20C, J20D
- Ford M2C-86B/C, M2C-134D
- CASE MS-1204, 1206, 1207, 1209
- CASE New Holland MAT 3535, 3526
- Caterpillar T0-2
- Allison C-4

HEALTH AND SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.

SAH LUBHIGAMIS (SOURE A. RADCLIFFE & SONS LTD) Gill Bridge Oil Works, Lowlands Road, MIRFIELD, West Yorkshire, WF14 8LU | Tel: +44 (0)1924 494371 Fax: +44 (0)1924 498940 | Email: enquiries@sarlubricants.co.uk Registered In England: 05866783 VAT Registration No: 889171963



- Massey Ferguson M1135, M1141 (Permatran III), M1143, M1145
- Volvo WB101 (VCE 97303)
- Sunstrand/Danfoss Hydrostatic Transmission Fluid
- JCMAS HK P-041 & P-042