Technical Data Sheet

SAR Lubricants

Last Updated: 10.10.2018 Code: AD00675

AUTOTRANS PRESTIGE is a very high performance, fully synthetic automatic transmission fluid designed to meet the exacting requirements of the latest transmissions found in many prestige and performance vehicles.

APPLICATION

Especially suitable for the ZF 6- and 8-speed transmissions fitted to many **BMW**, **AUDI**, **JAGUAR**, **LAND ROVER** and other prestige vehicles, as well as the 7-speed **MERCEDES-BENZ** 7G-Tronic 722.9 and hybrid 722.55 units, and meets and exceeds many other high performance OEM specifications as listed below.

BENEFITS

- Outstanding high torque capability and suitable for heavy loading and high operating temperatures.
- Low viscosity formulation to provide maximum transmission efficiency and fuel economy.
- Superior low temperature properties.
- Exceptional anti-shudder durability and stable frictional characteristics.
- Compatible with all types of transmission seal materials.
- Outstanding anti-wear protection and oxidation stability for longer component and fluid life.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- **BENTLEY** PY112995PA
- **BMW** ATF 3, ATF 3+
- **BMW** 83 22 0 144 137, 83 22 0 142 516
- BMW 83 22 2 305 397, 83 22 2 152 426
- **BMW** 83 22 0 397 114, 83 22 2 163 514, 83 22 289 720
- ATF M1375.4, M1375.6, M1375.8, L12108
- ATF 134, 3353
- **FIAT/CHRYSLER/JEEP** 68043742AA, 68157995AA
- HONDA ATF Type 3, Type 3.1

- JAGUAR C2C 8432, 02JDE 26444
- LAND ROVER TYK 500050, LR023288
- MASERATI 231603
- MB 236.12, 236.14, 236.41
- **PORSCHE** 000 043 304 00
- VW/AUDI G 055 162, G 055 005, G 052 533
- VW/AUDI G 060 162
- GM Dexron VI
- Not recommended for CVT or DCT transmissions

TYPICAL PROPERTIES

Appearance: Specific Gravity @ 15.6^oC: Pale amber 0.840 Kinematic Viscosity @ 100°C (cSt):

5.5 (typical)

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.

SAH LUBHIGAN IS (SOURE A. RADCLIFFE & SONE LTD) Gill Bridge Oil Works, Lowlands Road, MIRFIELD, West Yorkshire, WF14 8LU | Tel: +44 (0)1924 494371 Fax: +44 (0)1924 498940 | Email: enquiries@sarlubricants.co.uk Registered In England: 05866783 VAT Registration No: 889171963

