

Last Updated: 04.09.2015

Code: AG0650, AG0660

AXLE-PRO GEAR OILS 80w90 & 85w140 GL5 are premium quality, heavy-duty, hypoid axle and gear lubricants formulated to meet many of the latest OEM specifications and requirements, and incorporating the very latest additive technology combined with high quality solvent refined base stocks.

APPLICATION

Designed primarily for use in the latest designs of axles found in many late-model trucks and buses from a wide variety of manufacturers, as well as for all non-synchronized manual transmissions used in buses and heavy-duty trucks which require an API MT-1 specification lubricant.

BENEFITS

- Exceptional protection from wear over extended periods.
- Enhanced anti-corrosion and anti-oxidation characteristics for longer component life.
- Excellent load-carrying ability, even under arduous operating conditions.
- Formulated to impart improved performance and protection across a wide temperature range.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API GL-5, API MT-1
- MIL-PRF 2105E
- SAE J-2360
- SCANIA STO 1:0
- MACK GO-J
- Arvin Meritor Axles
- MAN 342 Type M2
- MB 235.20 (80w90)
- ZF TE-ML 05A, 07A, 12E, 16B, 17B, 19B, 21A

TYPICAL PROPERTIES

PRODUCT	AXLE-PRO 80w90 GL5	AXLE-PRO 85w140 GL5
Density @ 15.6°C	0.899	0.906
Viscosity @ 40°C	205.3 cSt	383.3 cSt
Viscosity @ 100°C	15.0 cSt	28.0 Cst
Viscosity Index	105	104

HEALTH AND SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.