

Last Updated: 08.01.2016  
Code: AE0624

**FLEETLUBE 10w40** is a high performance mixed fleet engine oil suitable for use in both petrol and diesel engines.

## APPLICATION

Suitable for use in all types of vehicles including heavy-duty diesels, light commercials, vans and cars, as well as agricultural equipment and off-highway vehicles where this specification of oil is required by the engine manufacturer.

Please note - Not suitable for vehicles fitted with emission-control after treatment systems, and which require a low SAPS lubricant. Please use Synmax Performance Plus E6 10w40 full synthetic oil for engines requiring this specification of engine oil.

## BENEFITS

- High shear stability
- Promotes easy starting in cold conditions
- Suitable for petrol and diesel engines
- Enhanced anti-wear performance for reduced engine wear
- Excellent sludge control for stop-go city motoring

## PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API CG-4/SJ
- ACEA E2, A3/B4
- Mercedes-Benz 228.1 / 229.1
- VW 500.00/505.00

## TYPICAL PROPERTIES

Specific Gravity @ 15.6°C:	0.888	Flash Point COC (°C):	220
Kinematic Viscosity @ 100°C (cSt):	13.82	Pour Point (°C):	-32
Kinematic Viscosity @ 40°C (cSt):	95.51	TBN mg KOH/g:	9.18
VI:	147		

## HEALTH AND SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.