

Last Updated: 08.11.2017

Product Codes: ML0032; ML0046; ML0068; ML 0100
ML 0220; ML 0320; ML 0460; ML 0680

MULTILUBE OILS are a range of premium quality, ashless lubricants formulated to meet the requirements of slideway, hydraulic systems, industrial gearboxes and general lubrication applications, and where one oil is required as a multifunctional lubricant.

APPLICATION

Use as received where applications require a zinc-free, multifunctional lubricant in an ISO 32, ISO 46, ISO 68, ISO 100, ISO 220, ISO 460 and ISO 680 viscosity, to the specifications listed below.

BENEFITS

- Multifunctional performance to help reduce lubricant inventories
- Outstanding cutting fluid compatibility
- Prevents any stick / slip on slideways
- Elevated corrosion resistance protects machine tools from rust
- Outstanding cutting fluid compatibility

TYPICAL PROPERTIES

	ISO 32	ISO 46	ISO 68	ISO 100	ISO 220	ISO 320	ISO 460	ISO 680
Viscosity @ 40°C	29 – 35	42 – 51	61 - 75	90 - 110	198 –242	288 –352	414 - 506	612 - 748
Specific Gravity @ 15.6°C	0.876	0.880	0.885	0.885	0.886	0.897	0.893	0.899

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.