# **Technical** Data Sheet

### **SAR** Lubricants

Last Updated: 18.01.2019 Product Code: PX0035

**PERFALUBE WCS** is a water soluble spinning lubricant specially designed for manufacturing wool and wool/nylon carpet yarns on the woollen system. Formulated to be suitable for scour dyeing processes and can also be removed by traditional scouring methods.

### APPLICATION

Perfalube WCS is water-soluble and therefore can be applied in solutions with water at any ratio.

On 100% wool and 80/20 wool/nylon blends application levels are normally 2.5-4% owf **Perfalube WCS**, water levels are normally similar to lubricant levels.

On 100% synthetic blends 0.7% - 1.0% owf is applied with 6-8% water.

### Scouring

On wool which contain less than 1% wool grease, satisfactory residues will be achieved with water only scours (scour dye). With higher grease levels, a more traditional scour will be necessary to remove the wool grease.

A typical scouring recipe on a four bowl scouring range would be:

	Temperature °C	Detergent
BOWL 1	55	1.0-2.0 g/l
BOWL 2	50	0.5-1.0 g/l
BOWL 3	50	-
BOWL 4	40	-

Only Bowl 1 requires additions as carry over to Bowl 2 will keep concentration level up. Additions of 750 grams detergent should be added after every 300 kilos of yarn.

A good quality highly active non-ionic detergent such as **Sardet 91/6** should be used.

The scouring recommendations are general. Blend aspects such as wool grease may require variation in detergent levels.

### **BENEFITS**

Carding and Spinning:	Perfalube WCS is highly antistatic and is therefore very effective at controlling fly	
	and eliminating static build up.	
Corrosion inhibition:	Perfalube WCS is inherently anti-corrosive and will not damage machinery.	
Scouring and Dyeing:Perfalube WCS being totally water soluble is eminently suitable for scour dyeing and can		
	also be removed by traditional scouring methods.	
Oxidation:	Perfalube WCS does not oxidise and will not yellow the fibre.	

Gill Bridge Oil Works, Lowlands Road, MIRFIELD, West Yorkshire, WF14 8LU | Tel: +44 (0)1924 494371 Fax: +44 (0)1924 498940 | Email: enquiries@sarlubricants.co.uk Registered In England: 05866783 VAT Registration No: 889171963

Cert. Number 12669

1/2

# **Technical** Data Sheet



### **TYPICAL PROPERTIES**

Appearance:	Colourless liquid
Specific Gravity:	1.15
Solubility:	Totally water soluble
Viscosity:	1050 mm²/s
pH (1% aqueous solution):	5 – 7
Activity:	70%

### PACKAGING

Perfalube WCS is available in 205 ltr drums, 1000 ltr IBC's and pumped bulk delivery.

#### **HANDLING PRECAUTIONS**

The usual precautions in handling chemicals should be observed and it is recommended that operatives should wear goggles and gloves when handling the concentrated product. Any contact with skin and eyes should be washed immediately with copious amounts of cold water. Please refer to Material Safety Data Sheet for further information.

### **HEALTH & SAFETY**

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.

Gill Bridge Oil Works, Lowlands Road, MIRFIELD, West Yorkshire, WF14 8LU | Tel: +44 (0)1924 494371 Fax: +44 (0)1924 498940 | Email: enquiries@sarlubricants.co.uk Registered In England: 05866783 VAT Registration No: 889171963

