Technical Data Sheet

SAR Lubricants

Last Updated: 10.09.2014 Product Code: GRO910

SARGREASE BLACKJACK 0 is a bitumen-based EP (extreme pressure) compound which combines highly effective lubrication and outstanding adhesive properties with excellent corrosion protection.

APPLICATION

Specially developed for the lubrication of all types and sizes of open gears, wire ropes, chains, flexible couplings etc. that are subjected to high loads in damp environments or open to adverse weather conditions.

Designed to provide economic application by brush or pump.

Please check compatibility before application and use in accordance with equipment manufacturers recommendations.

BENEFITS

- Easy to apply with outstanding adhesive properties on all types of metal surface
- Excellent corrosion protection protects components operating in wet conditions or open to the elements
- Highly effective EP and anti-wear performance

TYPICAL PROPERTIES

Appearance:	Black, heavy, tacky grease	Pour Point °C:	20
Viscosity@100°C (IP71):	1100-1300 cSt	Operating temp. range:	+5°C to +80°C
Flash Point °C:	270		

HEALTH AND SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.

Gill Bridge Oil Works, Lowlands Road, MIRFIELD, West Yorkshire, WF14 8LU | Tel: +44 (0)1924 494371 Fax: +44 (0)1924 498940 | Email: enquiries@sarlubricants.co.uk Registered In England: 05866783 VAT Registration No: 889171963



Cert. Number 12669