

Last Updated: 18.07.2017

Code: AE0768G

**SYNGEAR MTF 94** is a premium-quality, semi synthetic gearbox fluid designed for higher output manual transmissions and to meet the requirements of the manufacturers as listed below.

## APPLICATION

Primarily designed for manual transmissions which require a fluid to meet MTF 94 specification, particularly Rover vehicles fitted with PG1, PG2 and R65 gearboxes, such as many Rover 25, 45 and MGF models, as well as certain Land Rover, Honda and BMW/MINI vehicles which require this type of product.

## BENEFITS

- Excellent frictional characteristics for improved gear change, especially in colder conditions.
- Enhanced resistance to thermal degradation and the effects of oxidation.
- High viscosity index promotes stay-in-grade performance for longer fluid life.
- Excellent cold weather performance.

## PERFORMANCE PROFILE

Suitable for use where the following requirements are specified;

- SAE 75w80
- API GL-4
- Rover / Land Rover MTF 94
- Honda MTF94, MTF2
- BMW MTF LT-2

## TYPICAL PROPERTIES

Kinematic Viscosity @ 100°C (cSt):	10.3	SG @ 15.6°C:	0.874
Kinematic Viscosity @ 40°C (cSt):	64.5	Flash Point (COC):	>185°C
Viscosity Index:	147		

## HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.