

TURBOLUBE HD 10w40 is a semi-synthetic engine oil formulated to be suitable for many cars and light commercial vehicles, with either turbocharged or normally-aspirated engines.

APPLICATION

Recommended for use in many petrol and diesel vehicles, as well as vehicles powered by LPG, where this specification of oil is required.

BENEFITS

- Suitable for use in multi-valve engines with hydraulic lifters where this grade of oil is specified.
- Provides easy starting and quick circulation in cold conditions.
- Excellent anti-wear properties.
- Promotes longer oil drain periods where appropriate.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API SG/CF-4

TYPICAL PROPERTIES

- | | | | |
|--------------------------------|-------|------------------------|-----|
| • Specific Gravity @ 15.6°C: | 0.867 | • V.I. | 152 |
| • Kinematic Viscosity @ 100°C: | 13.6 | • Flashpoint (COC) °C: | 205 |
| • Kinematic Viscosity @ 40°C: | 89.9 | • Pour Point °C: | -30 |

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.