

Last Updated: 05.07.2016

Product Codes: SFH 0015, SFH 0022; SFH 0032; SFH 0046
SFH 0068; SFH 0100

SARFOOD PAO HYDRAULIC OILS are food grade and non-toxic, developed for hydraulic systems used in food, drink and pharmaceutical processing and packaging equipment. Full synthetic formulation suitable for other hydraulic systems where a clean, non-staining hydraulic oil is desired.

APPLICATION

SARFOOD PAO HYDRAULIC OILS are suitable for hydraulic systems designed to operate in applications where an ISO 15, 22, 32, 46, 68 & 100 oil viscosity grades are used. Follow manufacturer's instructions. It is important to purge the system of the previous oil prior to recharging with SARFOOD PAO HYDRAULIC OILS.

BENEFITS

- Low coefficient of friction provides excellent lubrication and reduces wear
- Fully synthetic oil provides extremely wide temperature stability and ensures greatly extended servicing intervals
- Low foaming reduces residue and scum build-up, which extends maintenance intervals.

TYPICAL PROPERTIES

ISO Grades	15, 22, 32, 46, 68 & 100
Appearance:	Clear Fluid
Base Fluid:	Polyalphaolefin
Temperature Range:	- 60°C to +240°C (depending on grade)

PERFORMANCE STANDARDS

- All ingredients are FDA listed
- Meets the requirements of NSF and InS H1 Guidelines
- Meets the USDA 1998 H1 Guidelines
- All grades contain no genetically-modified ingredients, and do not contain any nut oil or derivatives

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.